

SAFETY DATA SHEET

P.O. BOX 350

BRYN MAWR, PA 19010-0350

CHEMICAL NAME: Iron Titanate
COMMON/TRADE NAME: Ilmenite

SECTION 1 - IDENTIFICATION

Product Identifier Iron Titanate
Other Name(s) Ilmenite

Recommended use Manufacturing and Welding

Restrictions for use Commercial use only, not for human consumption

Manufacturer Name Chemalloy Company LLC Telephone (610) 527-3700

Address PO Box 350 **Fax No.** (610) 527-3878

Bryn Mawr, PA 19010 Emergency Phone (800) 424-9300 (Chemtrec)

Contract No. CCN 4453

SECTION 2 - HAZARD(S) IDENTIFICATION

Hazardous Classification Carcinogenicity (Category 1B)

per 29CFR 1910.1200 Specific target organ toxicity - single exposure (Category 3 - Respiratory Organs)

(Rev. July 1, 2012) Specific target organ toxicity - repeated exposure (Category 2 - Respiratory & Nervous System)

100% of ingredients consists of unknown acute toxicity

Other Hazards not classified None Known

Signal Word DANGER





Hazard pictograms

Hazard Statements

May cause cancer by inhalation.

May cause respiratory irritation

May cause damage to respiratory or nervous systems

Precautionary Statements

Prevention Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection.

Do Not breathe dust, fume, gas, mist, vapors or spray.

Use only in a well-ventilated area or outdoors.

Response If inhaled: Move person to fresh air and keep comfortable.

Seek medical advice/attention if feeling unwell, exposed or concerned.

Storage Store in a well-ventilated place in properly labelled, tightly sealed appropriate packaging.

Prohibit access to unauthorized use.

Disposal Dispose of contents/container in accordance with local, state and federal regulations.

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name		Formula	CAS No.	Concentration
Titanium Dioxide	Sast Sill	TiO ₂	13463-67-7	> 58 % and < 64 %
Iron Oxide		Fe_2O_3	1309-37-1	> 30 % and < 38 %
Aluminum Oxide		Al_2O_3	1344-28-1	> 0.9 % and < 2.5 %
Manganese Oxide		MnO	1344-43-0	> 1.0 % and < 1.6 %
Silicon Dioxide		SiO ₂	14808-60-7	> 0.6 % and < 1.5 %

Common Names/Synonyms Ilmenite

SDS 46.0 page 1 of 4

SECTION 4 - FIRST AID MEASURES

In case of inhalation If inhaled: Move person to fresh air and keep comfortable.

Seek medical advice/attention if feeling unwell, exposed or concerned. If victim is not breathing, and if assistance is trained, administer CPR.

In case of skin contact If after contact, skin becomes irritated, remove contaminated clothes from victim.

Wash the contaminated area with plenty of warm water and soap (for 15 minutes). If symptoms persist, seek medical attention and report substance contacting skin.

In case of eye contact Flush eyes immediately with plenty of flowing water for 15 minutes holding eyelids open.

If symptoms persist, seek medical attention and report substance irritating eyes.

In case of ingestion Obtain immediate medical attention and report substance ingested. Do not give an

unconscious victim anything to eat or drink, or try to induce vomiting.

Symptoms & Effects -acute May cause irritation of the respiratory system

Symptoms & Effects -chronic Longtime overexposure may cause silicosis or cancer due to the silica content, also

chronic overexposure to aluminum oxide may cause pneumoconiosis and neurotoxicity.

Immediate Medical Care Treat symptomatically.

SECTION 5 - FIREFIGHTING MEASURES

Extinguishing media Substance is not flammable or combustible, in case of fire use extinguishing media

appropriate for the surrounding environment (i.e. ABC dry chemical)

Special hazards arising

from substance or mixture

None Known

equipment & precautions for firefighters

Special protective Firefighters should wear full protective clothing and NIOSH approved self-contained breathing

apparatus.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and

emergency procedures

For non-emergency personnel: keep unprotected people away, allow only well trained

personnel wearing suitable protective clothing to respond to the incident.

For emergency responders: Avoid eye and skin contact; Do not inhale dust particles,

and avoid the formation of dust.

Methods and materials for containment and clean-up

Collect the spilled material in mechanical way, then place into a suitable, closed, properly labelled chemical waste container for disposal. During disposal wear suitable personal

protective equipment.

Environmental precautions Dispose of spillage and waste (product/packaging) in accordance with all applicable

environmental laws.

SECTION 7 - HANDLING AND STORAGE

Precautions for safe

Observe conventional hygiene precautions, and after work hours, wash hands thoroughly.

handling

Avoid the direct contact with the product.

Do not eat or smoke in the workplace. Ensure adequate ventilation and avoid formation of dust.

Use Personal Protective Equipment as detailed in Section 8.

Emptied containers may contain residues of product, which may be hazardous.

Conditions for Safe Storage, including

Keep product dry in suitable packaging, properly labeled and away from acids.

Keep product away from food, beverages, luxury goods, feed, and pharmaceuticals. any incompatibilities Follow all instructions on warning labels.

fire and explosion

Precautions against No special measures are required, substance will not burn.

SDS 46.0 page 2 of 4

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Hazardous Component	CAS	NO. OSHA PEL	ACGIH TLV
Titanium Dioxide	13463-67-7	15.0 mg/M³ TWA (Total Dust)	10.0 mg/M³ TWA
Iron Oxide	1309-37-1	15.0 mg/M³ TWA (Total Dust)	5.0 mg/M³ TWA (Respirable Particles)
Aluminum Oxide	1344-28-1	15.0 mg/M³ TWA (Total Dust)	1.0 mg/M³ TWA (Respirable Particles)
Manganese Oxide	1344-43-0	5.0 mg/M³ (Ceiling as Mn)	0.02 mg/M ³ TWA (Respirable Particles as Mi 0.1 mg/M ³ TWA (Inhalable Particles as Mn)
Silicon Dioxide	14808-60-7	0.1 mg/M ³ TWA (Respirable Dust)	0.025 mg/M³ TWA (Respirable Particles

Respiratory: NIOSH approved respirators should be used when mechanical controls are not feasible.

Hand: Protective gloves are recommended for handling this material.

Eye: ANSI approved eye protection is recommended when handling this material.

Other/ Clothing: Appropriate work place clothing should be worn when handling this material.

Engineering Local exhaust/ventilation should be used when feasible to control dust levels below acceptable

Controls: occupational exposure limits.

PHYSICAL STATE/APPEARANCE	ODOR	ODOR THRESHOLD	
Black to brown-red powder	No odor	No data available	
рН	MELTING PT	INITIAL BOILING PT	
No data available	Approx. 1402°C	No data available	
FLASH PT	EVAPORATION RATE	FLAMMABILITY (solid, gas)	
Not Applicable	Not Applicable	Non Flammable	
UEL / LEL	VAPOR PRESSURE	VAPOR DENSITY	
Not Applicable	Not Applicable	Not Applicable	
SPECIFIC GRAVITY/RELATIVE DENSITY	SOLUBILITY (water)	PARTITION COEFFICIENT	
$4.3 \text{ to } 5.0 \text{ (H}_2\text{O} = 1)$	Very Slight	Not Applicable	
AUTO IGNITION TEMPERATURE	DECOMPOSITION TEMPERATURE	VISCOSITY	
Not Applicable	No data available	Not Applicable	

SECTION 10 - STABILITY AND REACTIVITY

Reactivity None Known

Chemical Stability Stable at normal temperature & general work conditions

Possibility of Hazardous None Known

Reactions

Conditions to Avoid None Known

Incompatible Materials None Known

Hazardous Decomposition None known

Products

ACUTE TOXICITY	OXICITY LD ₆₀ (inhalation-r		LD ₅₀ (oral-rat)	ATE CALCULATIONS
None Known	No Data	a Available	No Data Available	Not Applicable
SKIN CORROSION/IRRITATION		SERIOUS EYE	DAMAGE/EYE IRRITATION	SKIN SENSITIZATION
None Known			None Known	None Known
GERM CELL MUTAGENICITY		CARCINOGENI	CITY (IARC, NTP, OSHA, ACGIH)	REPRODUCTIVE TOXICITY
None Known		1 ,	/ 1B: ACGIH classifies SiO ₂ as a spected human carcinogen	None Known
STOT-SINGLE EXPOSURE		STOT-REPEAT	ED EXPOSURE	ASPIRATION HAZARD
Category 3 - Respiratory		Category 2 - Respiratory		None Known

SECTION 11 -TOXICOLOGICAL INFORMATION (cont.)

Symptoms related to Physical, Chemical, Toxicological Characteristics

May cause irritation of the respiratory system

Immediate and Delayed effects from

short-term and long-term exposure

Longtime overexposure may cause silicosis or cancer due to the silica content, also chronic overexposure to aluminum oxide may cause pneumoconiosis and neurotoxicity.

SECTION 12	ECOLOGICAL	INFORMATION

ECOTOXICITY LC 50 (fish) EC 50 (crustaceans) NOEC (algae)

None Known No Data Available No Data Available No Data Available

Persistence and Degradability No data available

Bioaccumulative potential No data available

Mobility in Soil No data available

Other Adverse Effects No data available

SECTION 13 - DISPOSAL CONSIDERATIONS

Handling for Disposal Handle in accordance with good industrial hygiene and safety practice. Refer to protective

measures listed in Sections 7 and 8.

Methods of Disposal Dispose of spillage and waste (product/packaging) in accordance with all local/regional

national/international regulations.

SECTION 14 -TRANSPORT INFORMATION

Proper Shipping Name This material is not regulated by 49 CFR.

UN Number none Hazard Class

zard Class none Packing Group none

SECTION 15 - REGULATORY INFORMATION

TSCA Information

This chemical appears on the Toxic Substances Control Act (TSCA) inventory.

SARA Title III: Sec 302 Extremely Hazardous Substances, 40 CFR355

There are no extremely hazardous substances present in this material.

SARA Title III: Sec 311 and 312, MSDS Requirements

This material is subject to the reporting requirements for this regulation. Threshold planning quantity: 10,000 lbs.

SARA Title III: Sec 313, Toxic Chemicals Notification

This material is not subject to the annual reporting requirements for this regulation.

SECTION 16 -OTHER INFORMATION

Revision History 05/21/2015 - SDS formatted to 16-part GHS format, Supersedes 09/15/2012 MSDS revision

NOTE: The data contained in this Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. The information herein is based on technical data that Chemalloy believes to be reliable. It is intended to be used by persons with technical skill. Prior to use, users shall conduct their own investigation(s) to determine the suitability of the information for their particular purpose, and appropriate warnings and safe handling procedures should be provided to handlers and users. Any use of this data must be determined by the user to be in accordance with federal, state and local laws and regulations. Nothing herein is to be taken as a license to operate under or a recommendation to infringe any patents. Since conditions of use and suitability are beyond Chemalloy's control, any risks of use and suitability are therefor assumed by the user, and Chemalloy expressly disclaims all warranties, including warranties of merchantability and fitness for a particular purpose, express or implied, in respect to the use or suitability of the material.