

## **SAFETY DATA SHEET**

Last Updated: 04/17/2018

Section 1		IDENTIFICATION		
ThreadFit® Cutting Oil, Dark				
Manufacturer Information		Emergency Contact		
Smith-Cooper International		CHEMTREC		
2867 Vail Avenue		1300 Wilson Boulevard		
Commerce, CA 90040		Arlington, VA 22209-2380		
Phone: +1 (800) 766-0076		Phone: +1 (800) 424-9300		
Fax: +1 (323) 890-4456		International: +1 (703) 527-3887		
Product Use	Cutting Oil			
Section 2		HAZARDS IDENTIFICATION		
Hazard Classification	This product is not classified as hazardous according to 29 CFR 1910, amended to conform to the United Nations Global Harmonized System of Classification and Labeling of Chemicals (OSHA/GHS).			
Hazard Not Otherwise Classified	None as defined under 29 CFR 1910			
Hazard Statements	This product is not considered to be a carcinogen by IARC, ACGIH, NTP or OSHA. This material should not be used for any other purpose than the intended use in Section 1 without expert advice.			
Precautionary Statements	No hazards resulting from the material as supplied. Health injuries are not known or expected under normal use. Excessive exposure may result in eye, skin or respiratory irritation.			
Potential Health Effects	Routes of Exposure: Ingestion, Skin Contact, Eye Contact, Inhalation Eyes: Exposure may cause irritation Skin: Prolonged or excessive skin contact may cause mild skin irritation Inhalation: Prolonged or excessive inhalation may cause respiratory tract irritation Ingestion: No significant adverse effects are expected upon ingestion of this product. Small amounts (a tablespoon) swallowed during normal handling operations are not likely to cause injury; swallowing larger amounts than that may cause injury.  Signs and Symptoms: May cause eye/skin irritation. Inhalation of vapors in high concentrations may cause irritation of respiratory systems.			
Response	In the case of fire, refer to section 5. In the case of spill, refer to section 6 In the case where first aid is required, refer to section 4.			
Storage	Keep in a dry, cool well-ventilated place. Keep away from heat, sparks and open flame. Use care in handling/storage. Keep container closed when not in use. Do not store in unlabelled containers.			
Empty Container Warning	Empty containers may contain residue and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL GRIND OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS OR OTHER SOURCES OF IGNITION. Empty containers should be disposed of in accordance with all Federal, state and local regulations. Consider recycling where practical.			

Section 3 COMPOSITION/INFORMATION ON INGREDIENTS			
Component Name		CAS Number	Weight %
Severely Hydrotreated Base Oil		64742-54-7	87-93
1-Decene, Sulfurized		72162-15-3	7-13
Section 4			FIRST AID MEASURES
Inhalation	No specific treatment is necessary since this material is not likely to be hazardous by inhalation. If symptoms are experienced, remove source of contamination or move victim to fresh air.		
Skin	Wash contact area with soap and water. Get medical attention if irritation develops or persists.		
Eye	Flush eyes with water as a precaution. Get medical attention of irritation develops or persists.		
Ingestion	Have victim rinse mouth thoroughly with water. Drink water as a precaution. Do not induce vomiting without medical advice. If ingestion of a large amount does occur, seek medical attention.		
Symptoms	the respirator	May cause eye/skin irritation. Inhalation of vapors in high concentration may cause irritation of the respiratory system.	
General Advice	No hazards w effects develo	hich require special first aid. Not expected op.	to be toxic. Seek medical attention if ill
Section 5			FIRE FIGHTING MEASURES
Flash Point, ASTM D-9	92	Greater than 182.2 °C	
Extinguishing Media		Use water fog, foam, dry chemical or car	rbon dioxide.
Special Firefighting Procedures/Equipment		Wear suitable protective gear. In the event of fire, wear self contained breathing apparatus. Use MSHA/NIOSH (approved or equivalent).	
		None special. Irritating and/or toxic gase decomposition.	es may be emitted upon the products
Additional Information		Do not scatter spilled material with high pressure water streams.	
Section 6			ACCIDENTAL RELEASE MEASURES
Personal Precautions da		Keep unnecessary personnel away. Ensure adequate ventilation. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.	
Environmental Processitions		Prevent further leakage or spillage if safe to or sanitary sewer system. Notify appropria	te authorities if necessary.
Methods and Materials Use for Containment  Eliminate all ignition sources (NO SMOKING, FLARES, SPARKS OR FLAMI IMMEDIATE AREA). Stop leak if you can do so without risk. Dike the spil material where this is possible. Do not allow to enter sewers and water		so without risk. Dike the spilled	
Methods for Clean Up was tho		For larger spills, absorb with earth, sand or transfer to containers for later disposal. Do waterways. For small spills, wipe with an al thoroughly to remove residual contamination of the SDS.	o not allow the spill to enter sewers or bsorbent material. Clean surface ion. For waste disposal, see section 13
Section 7			HANDLING AND STORAGE
Handling P		Do not handle or store near open flames, s Protect material from direct sunlight. Do no or eyes. Handle open container with care. A product.	ot get this material in contact with skin Avoid breathing vapors or mists of this
		Keep in a dry, cool and well-ventilated plac open flame. Use care in handling/storage. I	

Section 8 EXPOSURE CONTROLS/ PERSONAL PROTECTION				
Exposure Guidelines				
Components	CAS-No.	Туре	Value	
Severely hydrotreated base oil	64742-54-7	ACGIH TLV	5 mg/m <sup>3</sup>	
1-Decene, sulfurized	72162-15-3	None Established	None Established	
Engineering Controls	Provide local and general exhaust to effectively remove and prevent buildup of any vapors or mists generated for the handling or use of this product.			
Personal Protection	Eye/Face Protection: Wear chemical goggles. If splashes occur, wear face shield Skin Protection: Wear suitable protective clothing including oil impervious gloves Respiratory Protection: No personal respiratory protective equipment normally required. If mist is generated (heating or spraying) and engineering controls are not sufficient, wear approved organic vapor respirator suitable for oil mist.			
General Measures	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking and/or smoking. Routinely wash work clothes and protective equipment to remove contaminants. Practice good housekeeping.			
Section 9		PHYSICAL ANI	CHEMICAL PROPERTIES	
Appearance: Dark brown liquid		Evaporation Rate: Not Determined		
Odor: Typical sulfurized oil odor		DMSO Extract (mineral oil only, IP-346 <3 % wt		
Odor Threshold: Not Available		Upper/lower Flammability LEL 0.9 UEL 7.0		
pH: Not Applicable		Vapor Pressure: <0.013 kPa (0.1 mm hG) at 20 °C		
Melting Point/Freezing Point: 0 °F		Vapor Density: (air=1) >2 at 101 kPa		
Boiling Point and Boiling Range: > 600 °F		Relative Density: 0.8735 specific gravity		
Flash Point: > 182.2 °C		Solubility: Negligible		
Partition Coefficient: > 3.5		Auto-Ignition Temperature: Not Determined		
Decomposition Temperature: Not Determined		Viscosity: approximately 35 cSt @	40 °C	
VOC Content: 1.0 g/L				
Section 10		ST.	ABILITY AND REACTIVITY	
Reactivity	See sub-sections below.			
Chemical Stability	Material is stable under normal conditions.			
Possibility of Hazardous Reactions	Will not occur.			
Conditions to Avoid	Heat, flames and sparks. None known. Avoid temperatures exceeding the flash point. This product may react with strong oxidizing agents.			

	Carbon oxides and sulfur oxides
Hazardous Decomposition	can som oxides and samar exides
Section 11	TOXICOLOGICAL INFORMATION
	Minimally toxic. Based on test data for structurally similar materials. Test(s)
Ingestion Toxicity	equivalent or similar to OECD Guideline 401
	Minimally taxia Dagad on tost data for structurally similar materials. Tost/o
Skin Toxicity	Minimally toxic. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 402
Skiii Toxicity	equivalent of similar to OECD Guideline 402
	May cause mild, short-lasting discomfort to eyes. Based on test data structurally
Eye Irritation	similar materials. Test(s) equivalent or similar to OECD Guideline 405
	Minimally taxia Dagad on tost data for structurally similar materials. Tost/s)
Respiratory Irritation	Minimally toxic. Based on test data for structurally similar materials. Test(s)
nespiratory irritation	equivalent or similar to OECD Guideline 403
	No data available
Chronic Toxicity	
Carcinogenicity	Not expected to cause cancer. Based on test data for structurally similar materials.
Carcinogenicity	Test(s) equivalent or similar to OECD Guideline 451 453
	For the product itself: Base oil severely refined: Not carcinogenic in animal studies.
Other	Representative material passes IP-346, Modified Ames test, and/or other screening
	tests.
Section 12	ECOLOGICAL INFORMATION
	Material not expected to be harmful to aquatic organisms.
Ecotoxicity	
	Biodegradation: Material – Expected to be inherently biodegradable
Degradability	blodegradation. Material – Expected to be inflerently blodegradable
,	
	Ecological injuries are not known or expected under normal use. An environmental
Other	hazard cannot be excluded in the event of unprofessional handling or disposal
Section 13	DISPOSAL CONSIDERATIONS
	Product is suitable for burning in an enclosed controlled burner for fuel value or
	disposal by supervised incineration at very high temperatures to prevent formation
Waste Disposal Method	of undesirable combustion products. Protect the environment. Dispose of used oil at
	designated sites. Minimize skin contact. Do not mix oils with solvents, brake fluids or
	coolants.
	RCRA Information. The unused product is not specifically listed by the EPA as a
	hazardous waste (40 CFR, Part 261D), nor is it formulated to contain materials which
	are listed as hazardous waste. However, after use it is the responsibility of the user
Section 14	to determine the products status for disposal.  TRANSPORT INFORMATION
	Not Regulated for Land Transport
UN Number	· ·
UN Proper Shipping Name	Not Applicable
- Cit i Topoi Simpping Italiic	
Transport Hazard Class	Not Regulated for Land Transport
Canadian Transportation of	Not Regulated for Land Transport
Dangerous Goods	Not hegalated for Early Transport
_	Not regulated for Sea Transport according to IMDG-Code
Marine Pollutants	Marine Pollutant: No

	Not regulated for Air Transport
Air (IATA)	Not regulated for Air Transport.
0 :: 15	
Section 15	REGULATORY INFORMATION
TSCA Status	All components are on the U. S. EPA TSCA Inventory list.
SARA 311/312 Reportable Hazard Categories	None Listed
California Prop 65	This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm. California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.
WHMIS DSL Status (Canada)	Not controlled
Section 16	OTHER INFORMATION
Additional Information  Prepared By	HMIS ratings:  Health = 1, Flammability = 1, Physical Hazard = 0, Personal Protection = B  NFPA ratings:  Health = 1, Flammability = 1, Instability = 0
	There are no Red List materials included in this product.  Human Resource Department
Revised Date	September 8, 2015
Disclaimer	Although the information and recommendations set forth herein are presented in good faith and believed to be correct as of the date hereof, Smith-Cooper International makes no representations as to the completeness or accuracy thereof. Smith-Cooper International makes no warranty whatsoever, expressed or implied, of merchantability or fitness for the particular purpose since the conditions of use are beyond our control. Smith-Cooper International no responsibility for injury to recipient or to third persons for any damage to any property and recipient.