SAFETY DATA SHEET

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product: Grey Underglaze

Product Use: Ceramic decorating paint

Date Prepared: July 18 2017

@PSH

Manufacturer and Supplier:

The Pottery Supply House Limited

1120 Speers Road

Oakville, ON, Canada L6L 2X4

Tel.: 1-800-465-8544

Emergency Tel: Not Available

SECTION 2. HAZARDS IDENTIFICATION



Carcinogen Category 1A

Specific Target Organ Toxicity - Repeated Exposure Category 1

Warning: May cause cancer by inhalation.

Causes damage to lungs through prolonged or repeated exposure by inhalation.

Do not breathe dust mist or fume.

In case of inadequate ventilation, wear respiratory protection.

Do not ingest.

Emergency Overview: Not acutely hazardous. Chronic exposure to respirable dusts or mists may cause lung disease.

SECTION 3. COMPOSITION INFORMATION ON INGREDIENTS

Component	CAS#	Percentage	LD 50	LC 50
Crystalline silica (quartz)	14808-60-7	0.1 - 1	>22,500 mg/kg (Oral, Rat)	Not available
Frit ¹	65997-18-4	5 – 10	2000 mg/kg (Oral, rat)	Not available
Zircon	14940-68-2	15 – 40	990 to 2,290 mg/kg (Oral, Mouse, Rat, GuineaPig)	> 6 mg/L
Cobalt silicate olivine	68187-40-6	0.1 – 1	1630 mg/kg (Oral, rat)	>5.3 mg/L air (rats; 4 hours)
Iron chromite spinel	1308-31-2	3 - 7	Not available	Not available
Kaolin ²	1332-58-7	3 - 7	Not available	Not available
Kaolin ²		ļ	- 100 41 41-40-0	1

^{1.} Glass containing fused oxides of aluminum, boron, calcium, silicon and sodium. 2. Aluminum silicate mineral.

SECTION 4. FIRST AID MEASURES

Procedures

Skin contact (mechanical irritant): Wash off immediately with soap and plenty of water. Remove and wash contaminated clothing before re-use. If symptoms persist, call a physician.

Eye contact (mechanical irritant): Wash immediately with plenty of water. If irritation persists, seek medical attention.

Inhalation: No specific first-aid is generally necessary since the adverse health effects associated with exposure to crystalline silica (quartz) result from chronic exposures.

Ingestion: Drink plenty of water. Do not induce vomiting. Consult a physician if necessary.

SECTION 5. FIRE FIGHTING MEASURES

Conditions of flammability: Not flammable.

Extinguishing media, means of extinction: Product is not flammable, combustible or explosive. Use extinguishing media appropriate for surrounding fire.

Hazardous combustion products: Metal compounds. Oxides of carbon, sodium and irritating gases (<1%, total) may be liberated.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Procedures to be followed in case of leak or spill: Discard any product, residue, disposable container or liner in compliance with regulatory requirements.

SECTION 7. HANDLING AND STORAGE

Handling procedures and equipment: Avoid dust/mist formation. Do not breathe dust or mist. If spraying, use adequate exhaust ventilation. Keep airborne dust/mist concentrations below permissible exposure limits. In case of insufficient ventilation, wear a respirator approved for silica dust when spraying. Practice good housekeeping. Do not permit dust to collect on walls, floors, sills, ledges, machinery, or equipment. When firing, use adequate kiln ventilation. **Storage:** No special requirement. To prevent possible container damage, keep from freezing.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure limits: TWA (Ontario)

Crystalline silica (quartz)	0.1 mg/m³ (respirable)	
Frit	10 mg/m³ (PNOS*)	
Zircon	5 mg/m3 (zirconium compound, as Zr)	
Cobalt silicate olivine	0.02 mg/m3 (inorganic cobalt compound) 0.1 mg/m³ (crystalline silica, respirable)	
Iron chromite spinel	0.5 mg/m³ as Cr III compound 5 mg/m³ as Fe2O3	
Kaolin	2 mg/m ³	
* PNOS: Particles (insoluble or poorly soluble) not otherwise specified		

Specific engineering controls to be used: Ventilation must be adequate to maintain the ambient workplace atmosphere below the exposure limit(s). Ensure that eye washing facilities are nearby. If spraying, use a ventilated spray booth to minimize exposure to respirable mist. When firing, use adequate kiln ventilation.

Personal protective equipment to be used: In case of exposure to dust/mist, and in any case if such exposure is above regulatory limits (see above), wear a personal respirator.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid/solid suspension.

Odour and appearance: Opaque, pale grey fluid with mild odour.

Odour threshold: Not available.
Specific gravity: Approximately 1.6.
Vapour pressure: Not available.
Vapour density: Not available.
Evaporation rate: Not available.

Boiling point: About 100°C for the liquid (water) portion. >1250°C for the solids portion.

Freezing point: About 0°C for the liquid (water) portion.

Decomposition temperature: Not available.

PH: Not available.

Solubility: Solids portion is insoluble in water.

Partition coefficient: Unavailable.

Viscosity: Not available

Coefficient of water/oil distribution: Not available. **Flash point and method of determination:** Not applicable.

Upper flammable limit: Not applicable. Lower flammable limit: Not applicable. Auto-ignition temperature: Not applicable.

Explosion data – sensitivity to mechanical impact: Not explosive. Not sensitive.

Explosion data – sensitivity to static discharge: Not explosive. Not sensitive.

SECTION 10. STABILITY AND REACTIVITY

Reactivity: Not reactive under normal use conditions. **Chemical stability:** Stable under normal use conditions.

Conditions to avoid: Contact with powerful oxidizing agents may cause fires.

Incompatible materials: Powerful oxidizing such as fluorine, chlorine trifluoride, and oxygen difluoride. Chromite can react at high temperature with molten alkalis and alkali vapors forming water-soluble, hazardous chromium salts.

Hazardous decomposition products: No decomposition if stored normally. Thermal decomposition can lead to release of

irritating gases and vapors including oxides of carbon, nitrogen, and sulfur as well as toxic metal compounds.

Possibility of Hazardous reactions: Not under normal use conditions.

SECTION 11, TOXICOLOGICAL INFORMATION

Route of entry Skin contact: Prolonged skin contact may cause skin irritation.

Skin absorption: Not absorbed through the skin. **Eye contact:** May cause abrasion of the cornea.

Inhalation: Contains crystalline silica (<1%). Chronic exposure may cause silicosis,

cancer and other disorders. Dust or fumes from firing are irritating to the respiratory tract. The risk of exposure to respirable dust is low given that this product is typically applied by brush, contains a binder that reduces the risk of dusting when dry, and has a very low crystalline silica content.

Ingestion: Not acutely hazardous. May cause gastrointestinal upset.

Effects of acute exposure to product: No effects expected.

Effects of chronic exposure to product: Excessive inhalation of fumes or dust may cause chemical pneumonitis, cyanosis, and pulmonary edema. Respirable crystalline silica (quartz) can cause:

A. SILICOSIS The major concern is silicosis, caused by the inhalation and retention of respirable crystalline silica dust. Chronic or Ordinary Silicosis is the most common form of silicosis, and can occur after many years of exposure to relatively low levels of airborne respirable crystalline silica dust. Symptoms, if present, are shortness of breath, wheezing, cough and sputum production and may be associated with decreased and disabling lung function and death. It may lead to heart disease secondary to the lung disease.

- B. CANCER IARC The International Agency for Research on Cancer ("IARC") concluded that there was "sufficient evidence in humans for the carcinogenicity of crystalline silica in the forms of quartz or cristobalite from occupational sources"
- C. AUTOIMMUNE DISEASES Several studies have reported excess cases of several autoimmune disorders, -- scleroderma, systemic lupus erythematosus, rheumatoid arthritis -- among silica-exposed workers.
- D. TUBERCULOSIS Individuals with silicosis are at increased risk to develop pulmonary tuberculosis, if exposed to persons with tuberculosis.
- E. KIDNEY DISEASE Several studies have reported excess cases of kidney diseases, including end stage renal disease, among silica-exposed workers.
- F. NON-MALIGNANT RESPIRATORY DISEASES There are studies that disclose an association between dusts found in various mining occupations and non-malignant respiratory diseases including chronic bronchitis, emphysema and small airways disease, particularly among smokers.

Irritancy of the product: Not a likely irritant.
Sensitization of the product: No known effects.

Carcinogenicity of the product: See effects of chronic exposure, above. Zircon contains trace quantities of naturally occurring radioactive uranium, thorium and radium (106-120 Pico curies/gram). Overexposure to respirable dusts containing radioactive uranium, thorium and radium may cause lung cancer.

Reproductive toxicity: No known effects.

Teratogenicity: No known effects. Mutagenicity: No known effects.

Name of toxicologically synergistic products: None known.

LD50: Not established for this product. See Section 3 for information on ingredients. **LC50:** Not established for this product. See Section 3 for information on ingredients.

SECTION 12. ECOLOGICAL INFORMATION

No data available for this product. No specific adverse effect known.

SECTION 13. DISPOSAL CONSIDERATIONS

Waste Disposal: Waste must be disposed of in accordance with federal, provincial and local environmental control regulations. Where possible recycling is preferred to disposal or incineration.

SECTION 14. TRANSPORT INFORMATION

Special shipping information: None.

SECTION 15. REGULATORY INFORMATION

This product has been classified

Carcinogen Category 1A

Specific Target Organ Toxicity - Repeated Exposure Category 1

in accordance with the hazard criteria of WHMIS 2015 and the SDS contains all of the information required by those regulations.

SECTION 16. OTHER INOFRMATION

Preparation information: Prepared by Jon Walls.

Contact information: Jon Walls. Telephone: 1-800-465-8544 ext.223

e-mail: jwalls@psh.ca

Date of preparation: July 18, 2017

Although reasonable care has been taken in the preparation of the information contained herein, The Pottery Supply House extends no warranties, makes no representation and assumes no responsibility as to the accuracy or suitability of such information for application to purchaser's intended purposes or for consequences of its use.