# SAFETY DATA SHEET

Revision Date 11/06/2017 Print Date 05/17/2018

### 1. PRODUCT AND COMPANY IDENTIFICATION

1.1 **Product identifiers** 

Product name

Nafion® perfluorinated resin, aqueous dispersion

**Product Number** 

527106

Brand

Aldrich

CAS-No.

1 31175-20-9

Relevant identified uses of the substance or mixture and uses advised against 1.2

Identified uses

: Laboratory chemicals, Synthesis of substances

Details of the supplier of the safety data sheet

Company

Sigma-Aldrich Canada Co. 2149 Winston Park Drive **OAKVILLE ON L6H 6J8** 

CANADA

Telephone

+1 9058299500

Fax

+1 9058299292

**Emergency telephone number** 

Emergency Phone #

: +1-703-527-3887 (CHEMTREC)

### 2. HAZARDS IDENTIFICATION

#### Classification of the substance or mixture

GHS Classification in accordance with Hazardous Products Regulations (HPR) (SOR/2015-17)

Eye irritation (Category 2A), H319

Specific target organ toxicity - single exposure (Category 1), H370

For the full text of the H-Statements mentioned in this Section, see Section 16.

#### GHS Label elements, including precautionary statements 2.2

Pictogram

Signal word

Danger

Hazard statement(s)

H319 Causes serious eye irritation. H370 Causes damage to organs.

Precautionary statement(s) P260

Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear eye protection/ face protection.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Call a POISON CENTER/doctor.

P308 + P311 P337 + P313 If eye irritation persists: Get medical advice/ attention.

P405 Store locked up.

P501 Dispose of contents/ container to an approved waste disposal plant.

Aldrich - 527106

Page 1 of 11

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.2 Mixtures

Synonyms

: Nafion® DE 1021

Hazardous components

Zardous components Component		Classification	Concentration*	
Methanol				
CAS-No.	67-56-1	Flam. Liq. 2; Acute Tox. 3;	1 - 5 %	
EC-No.	200-659-6	STOT SE 1; H225, H301 +		
index-No.	603-001-00-X	H311 + H331, H370		
Registration number	01-2119433307-44-XXXX		<u> </u>	
* Weight percent				
2-Propanol				
CAS-No.	67-63-0	Flam. Liq. 2; Eye Irrit, 2A;	1 - 5 %	
EC-No.	200-661-7	STOT SE 3; H225, H319,		
Index-No.	603-117-00-0	H336		
* Weight percent				
n-Propanol				
CAS-No.	71-23-8	Flam. Liq. 2; Eye Dam. 1;	1 - 5 %	
EC-No.	200-746-9	STOT SE 3; H225, H318,		
Index-No.	603-003-00-0	H336		

For the full text of the H-Statements mentioned in this Section, see Section 16.

# 4. FIRST AID MEASURES

### 4.1 Description of first aid measures

### General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

### In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

### In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

### If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

# 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

# 4.3 Indication of any immediate medical attention and special treatment needed No data available

### **5. FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media

#### Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

### 5.2 Special hazards arising from the substance or mixture

No data available

#### 5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

#### 5.4 Further information

No data available

### 6. ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas.

For personal protection see section 8.

#### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

### 6.3 Methods and materials for containment and cleaning up

Soak up with inert absorbent material and dispose of as hazardous waste. Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For disposal see section 13.

### 7. HANDLING AND STORAGE

### 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

For precautions see section 2.2.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Storage class (TRGS 510): 10: Combustible liquids

### .3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters

Components with workplace control parameters

Components	CAS-No.	Value	Control parameters	Basis	
Methanol	67-56-1	TWA	200.000000 ppm 262.000000 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)	
Remarks	Substance may be readily absorbed through intact skin				
		STEL	250.000000 ppm 328.000000 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)	
	Substance may be readily absorbed through intact skin				

Page 3 of 11

		TWA	200.000000 ppm	Canada, British Columbia OEL			
<del></del>	Contributes	Contributes significantly to the overall exposure by the skin route.					
		STEL	250.000000 ppm	Canada. British Columbia OEL			
	Contributes	Contributes significantly to the overall exposure by the skin route.					
		TWAEV	200.000000 ppm 262.000000 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants			
	Skin (percu	taneous)					
		STEV	250.000000 ppm 328.000000 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants			
_	Skin (percu	taneous)	!				
		TWA	200 ppm 262 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)			
	Substance	may be read	ily absorbed throu	ugh intact skin			
		STEL	250 ppm 328 mg/m3	Canada, Alberta, Occupational Health and Safety Code (table 2: OEL)			
	Substance	Substance may be readily absorbed through intact skin					
		TWA	200 ppm	Canada. British Columbia OEL			
	Contributes	Contributes significantly to the overall exposure by the skin route.					
		STEL	250 ppm	Canada. British Columbia OEL			
	Contributes	Contributes significantly to the overall exposure by the skin route.					
		TWAEV	200 ppm 262 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants			
	Skin (percut	laneous)					
		STEV	250 ppm 328 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants			
	Skin (percut	taneous)	I	1			
		TWA	200.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)			
		STEL	250.000000	USA. ACGIH Threshold Limit Values (TLV)			

Aldrich - 527106 Page 4 of 11

			ppm	
		TWA	200 ppm	USA. ACGIH Threshold Limit Values (TLV)
		STEL	250 ppm	USA. ACGIH Threshold Limit Values (TLV)
2-Propanol 67	67-63-0	TWAEV	400 ppm 983 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		TWAEV	400.000000 ppm 983.000000 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
		TWA	200 ppm	Canada, British Columbia OEL
		TWA	200.000000 ppm	Canada. British Columbia OEL
		STEL	400 ppm	Canada. British Columbia OEL
		STEL	400.000000 ppm	Canada. British Columbia OEL
		TWAEV	200.000000 ppm	Canada. Ontario OELs
		STEV	400.000000 ppm	Canada. Ontario OELs
		STEL	400.000000 ppm 984.000000 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
		STEL	400 ppm 984 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
		TWA	200.000000 ppm 492.000000 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
		TWA	200 ppm 492 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
		STEL	500.000000 ppm 1,230.000000 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
		TWA	400.000000 ppm 983.000000 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
		STEV	500.000000 ppm 1,230.000000 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants

Aldrich - 527106 Page 5 of 11

		STEV	500 ppm 1,230 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants			
		TWA	200.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)			
		TWA	200 ppm	USA. ACGIH Threshold Limit Values (TLV)			
		STEL	400 ppm	USA. ACGIH Threshold Limit Values (TLV)			
		STEL	400.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)			
n-Propanol	71-23-8	TWA	200.000000 ppm 492.000000 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)			
Remarks	Substance	may be read	dily absorbed throu	gh intact skin			
		STEL	250.000000 ppm 614.000000 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)			
	Substance	may be read	dily absorbed throu	gh intact skin			
		STEL	400.000000 ppm 984.000000 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)			
		Occupational exposure limit is based on irritation effects and its adjustment to compensate for unusual work schedules is not required					
		STEL	400 ppm 984 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)			
	Occupational exposure limit is based on irritation effects and its adjustment to compensate for unusual work schedules is not required						
		TWA	200.000000 ppm 492.000000 mg/m3	Canada. Alberta. Occupational Health and Safety Code (table 2: OEL)			
	Occupational exposure limit is based on irritation effects and its adjustment to compensate for unusual work schedules is not required						
		TWA	200 ppm 492 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)			
	Occupational exposure limit is based on irritation effects and its adjustment to compensate for unusual work schedules is not required						
		TWA	100 ppm	Canada. British Columbia OEL			
		TWA	100.000000	Canada, British Columbia OEL			

Aldrich - 527106 Page 6 of 11

	TWAE	V 100.000000 ppm	Canada. Ontario OELs
	STEV	250.000000 ppm 615.000000 mg/m3	Canada. Ontario OELs
	TWAE	V 200 ppm 492 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
<del></del>	Skin (percutaneous)		
	TWAE	V 200.000000 ppm 492.000000 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
	Skin (percutaneous)	_	
	STEV	250 ppm 614 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
	Skin (percutaneous)		
	STEV	250.000000 ppm 614.000000 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
	Skin (percutaneous)		<u>.</u>
10	TWA	100 ppm	USA. ACGIH Threshold Limit Values (TLV)
	TWA	100.000000 ppm	USA. ACGIH Threshold Limit Values (TLV)

### 8.2 Exposure controls

### Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

### Personal protective equipment

# Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

### Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

### **Body Protection**

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

108 °C (226 °F) at 1,013 hPa (760 mmHg)

### 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

a) Appearance Form: liquid
 b) Odour No data available
 c) Odour Threshold No data available
 d) pH No data available
 e) Melting point/freezing No data available

f) Initial boiling point and

point

g) Flash point

boiling range

110 °C (230 °F) - closed cup

h) Evaporation rate No data available
i) Flammability (solid, gas) No data available
j) Upper/lower No data available
flammability or
explosive limits

k) Vapour pressure No data available
 l) Vapour density No data available
 m) Relative density 1.050 g/cm3
 n) Water solubility No data available
 o) Partition coefficient: n-No data available

 Partition coefficient: noctanol/water

p) Auto-ignition temperature No data available

 Decomposition temperature No data available

Viscosity
 Explosive properties

No data available No data available

Oxidizing properties No data available

### 9.2 Other safety information

No data available

### 10. STABILITY AND REACTIVITY

### 10.1 Reactivity

No data available

### 10.2 Chemical stability

Stable under recommended storage conditions.

### 10.3 Possibility of hazardous reactions

No data available

Page 8 of 11

# 10.4 Conditions to avoid

No data available

#### 10.5 Incompatible materials

Aluminium, Acids, Oxidizing agents, Alkali metals, Strong oxidizing agents, Halogenated compounds, Strong acids, Acid chlorides, Acid anhydrides, Reducing agents, Strong reducing agents, Phosphorus halides

### 10.6 Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides, Sulphur oxides

Other decomposition products - No data available

In the event of fire: see section 5

### 11. TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects

#### Acute toxicity

No data available

Inhalation: No data available

Dermal: No data available

No data available

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

#### Carcinogenicity

IARC:

No component of this product present at levels greater than or equal to 0.1% is identified as

probable, possible or confirmed human carcinogen by IARC.

ACGIH:

No component of this product present at levels greater than or equal to 0.1% is identified as a

carcinogen or potential carcinogen by ACGIH.

### Reproductive toxicity

No data available

No data available

### Specific target organ toxicity - single exposure

No data available

### Specific target organ toxicity - repeated exposure

No data available

### **Aspiration hazard**

No data available

### Additional Information

RTECS: Not available

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Stomach - Irregularities - Based on Human Evidence (Ethanesulfonic acid, 2-[1-[difluoro](1,2,2-

trifluoroethenyl)oxy]methyl]-1,2,2,2-tetrafluoroe thoxy]-1,1,2,2-tetrafluoro-, polymer)

Stomach - Irregularities - Based on Human Evidence (Methanol)

Kidney - Irregularities - Based on Human Evidence (2-Propanol)

Eyes - Eye disease - Based on Human Evidence (Dimethyl sulfoxide)

Stomach - Irregularities - Based on Human Evidence (n-Propanol)

### 12. ECOLOGICAL INFORMATION

#### 12.1 Toxicity

No data available

#### 12.2 Persistence and degradability

No data available

### 12.3 Bioaccumulative potential

No data available

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

### 12.6 Other adverse effects

No data available

# 13. DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods

#### **Product**

Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

#### Contaminated packaging

Dispose of as unused product.

### 14. TRANSPORT INFORMATION

### TDG (Canada)

Not dangerous goods

#### IMDG

Not dangerous goods

#### IATA

Not dangerous goods

### 15. REGULATORY INFORMATION

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

### **16. OTHER INFORMATION**

Full text of H-Statements referred to under sections 2 and 3.

Acute Tox.

Acute toxicity

Eye Dam.

Serious eye damage

Eye Irrit.

Eye irritation

Flam, Liq.

Flammable liquids

H225

Highly flammable liquid and vapour.

H301 + H311 + H331

Toxic if swallowed, in contact with skin or if inhaled.

H318

Causes serious eye damage.

Causes damage to organs.

H319 H336 Causes serious eye irritation. May cause drowsiness or dizzīness.

H370

Aldrich - 527106

Page 10 of 11

STOT SE Specific target organ toxicity - single exposure

#### Further information

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Version: 4.3

Revision Date: 11/06/2017

Print Date: 05/17/2018

Page 11 of 11

Aldrich - 527106

