## **AZ nLOF 2035 PHOTORESIST**

(US)



Substance key: 000000065924

**REVISION DATE: 10/20/2008** Version Print Date: 10/20/2008

## Section 01 - Product Information

Identification of the AZ Electronic Materials USA Corp.

> company: 70 Meister Avenue Somerville, NJ 08876

Telephone No.: 800-515-4164

Information on the substance/preparation

Product Safety: 908-429-3562

Emergency Tel. number: 800-424-9300 CHEMTREC

Trade name: **AZ nLOF 2035 PHOTORESIST** (US)

# **Section 02 - Composition information**

# Hazardous ingredients:

Chemical Name	CAS-no. (Trade	Concentration [%]
	secret no.)	
1-Methoxy-2-propanol acetate	108-65-6	< 65.00
Modified melamine -formaldehyde resin	67829000004-	< 5.00
	5594P	
Phenolic polyol	67829000004-	< 2.00
	5798P	

#### Non-hazardous ingredients:

Chemical Name	CAS-no. (Trade secret no.)	Concentration [%]
Cresol novolak resin	67829000004- 5792P	28.00
Benzeneacetonitrile derivative	67829000004- 5765P	>= 2.00

# Section 03 - Hazardous identification

Clear, pale yellow liquid., Strong characteristic odor., Partially **Emergency overview:** 

> dissolves in water leaving a floating viscous mass., OSHA combustible liquid; DOT flammable liquid., Irritating on contact

or inhalation.

## **Expected route of entry**

#### AZ nLOF 2035 PHOTORESIST



Substance key: 000000065924 REVISION DATE: 10/20/2008

(US)

Version Print Date: 10/20/2008

Skin contact: yes Ingestion: no Inhalation: yes

**Eye contact:** Contact with liquid and vapors.

Skin absorption: yes

Health effects of exposure:

## **Component information:**

Eye: Causes eye irritation. Skin: Causes skin irritation. Ingestion: May be harmful if swallowed. Inhalation: Single exposure unlikely to be hazardous. High vapor concentration causes irritation to the nose, throat, and lungs. Systemic Effects: No hazard in normal industrial use. Reproductive & birth defects: Exposures having no adverse effect on the mother should have no effect on the fetus.

#### 1-Methoxy-2-propanol acetate (108-65-6)

1-Methoxy-2-propanol acetate (PGMEA) can cause skin, eye, and respiratory irritation. Extreme or prolonged exposure may cause gastric and central nervous system effects. Long term, high level exposure to PGMEA has resulted in adverse effects to the livers and kidneys of experimental animals. PGMEA is readily absorbed through intact skin.

**Known effects on other** Preexisting skin, eye, and respiratory conditions may be

**illnesses:** aggravated.

Listed carcinogen: IARC: NO NTP: NO OSHA: NO

HMIS:

Health: 2 Flammability: 2 Reactivity: 0 Personal protection: X

NFPA:

Health: 2 Flammability: 2 Reactivity: 0 Special notice: NONE

# Section 04 - First aid measures

After inhalation: Remove victim to fresh air.

Consult physician if irritation occurs.

After contact with skin: Immediately remove contaminated clothing. Flush affected

area thoroughly with water. After flushing with water, remove residue with soap and water. If necessary, clean area with a cloth or paper towel wetted with acetone. Assure adequate ventilation. Dispose of cloth/towel in a suitable receptacle. Consult physician if exposure is extensive or if irritation occurs.

After contact with eyes: Flush thoroughly with water for 15 minutes. Get immediate

medical help.

#### AZ nLOF 2035 PHOTORESIST

(US)



Substance key: 000000065924 REVISION DATE: 10/20/2008 Version Print Date: 10/20/2008

After ingestion: If person is conscious, give water or milk to dilute stomach

contents.

Never give anything by mouth to an unconscious person.

Consult physician.

Advice to doctor /

Treatment:

Administer oxygen if there is difficulty in breathing.

## Section 05 - Fire fighting measures

Flash point: 118 °F

Method: closed cup

Suitable extinguishing

media:

procedure:

Carbon dioxide, water, alcohol resistant foam, dry chemical.

Special fire fighting

Use self-contained breathing apparatus and full protective

clothing. Use water spray to cool drums in fire area.

Special hazards from the

substance itself, its

combustion products or

from its vapours:

Thermal decomposition may generate carbon dioxide, carbon

monoxide, and oxides of nitrogen and sulfur.

Unusual fire and

explosion hazards:

Solvent vapors., Emits toxic fumes under fire conditions.

#### Section 06 - Accidental release measures

Steps to be taken in case

of spill or leak:

Wearing appropriate personal protective equipment, contain spill, ventilate area of spill or leak, remove all sparking devices or ignition sources, collect onto inert absorbent, and place in a

suitable container.

## Section 07 - Handling and Storage

## Advice on safe handling:

Keep away from heat and flame.

Wash thoroughly after handling.

Keep container closed.

Avoid breathing vapors and contact with skin, eyes, and clothing.

Use only with adequate ventilation and proper protective eyewear, gloves, and clothing.

## Further information for storage conditions:

Store at appropriate temperature. See label for details.

Store in original container.

## **AZ nLOF 2035 PHOTORESIST**

(US)



Substance key: 000000065924 REVISION DATE: 10/20/2008

Version Print Date: 10/20/2008

May liberate combustible solvent vapors.

Transport and store under dry conditions tightly closed.

## Section 08 - Exposure Control / personal protection

#### Occupational exposure limits:

Components	CAS	Regulatory list	Type of value	Value 1	Value 2
	number				
1-Methoxy-2-propanol acetate	108-65-6	ZUS_AIHAS	Time Weighted Average (TWA)	50 ppm	

**Respiratory protection:** Chemical cartridge respirator recommended for exposures

Use local exhaust ventilation.

exceeding TLV.

Hand protection: Solvent Resistant Gloves.

**Eye protection:** Safety eyewear to protect against splashes.

**Body protection:** Clothing suitable to prevent skin contact.

**Body protection:** Clothing suitable to prevent skin contact.

Additional advice on

system design:

IDLH: Listed: no

# Section 09 - Physical and chemical properties

Form: Liquid

Color: Clear, amber-red

**Odor:** Strong, characteristic odor.

**pH value:** Not applicable

**Solubility in water:** The solvent is water soluble but the product forms two layers.

**Density:** 1.052 g/cm3

Starts to boil: from 134 °C

**Evaporation number:** 0.33 (PGMEA)

Vapor pressure: 2.41 Torr

Method: calculated

## **AZ nLOF 2035 PHOTORESIST**



Substance key: 000000065924

**REVISION DATE: 10/20/2008** Print Date: 10/20/2008 Version

(US)

79 mPas Viscosity, dynamic:

> Loss on drying: 64 %

## Section 10 - Stability and reactivity

Hazardous reactions: Stable.

Hazardous polymerization: Will not occur.

> Conditions to avoid: Avoid contact with oxidizing agents. Avoid contact with strong

> > acids. Avoid contact with alkaline materials.

# Section 11 - Toxicological information

Based on data from components this material is considered, Acute oral toxicity:

not harmful (rat acute oral LD50 > 5000 mg/kg).

Acute inhalation toxicity

Based on data from components, this material is considered. not harmful (LC50 greater than 10,000 ppm or 200 mg/L), Based on component data, material is considered irritating to

the respiratory tract.

Acute dermal toxicity: The acute toxicity via the dermal route of exposure, based on

component data, suggest that this material should be

considered not harmful (rabbit or rat dermal LD50 greater than

2000 mg/kg)

Skin irritation: Based on data from components, this material is considered a

non-irritant; however, the product is considered to be a human

skin irritant.

Eye irritation: Based on data from components, this material is considered to

be a mild eye irritant.

Further information: Long term, high level exposure to PGMEA has resulted in

> adverse effects to the livers and kidneys of experimental animals., Testing of components suggest no genotoxic hazard.

1-Methoxy-2-propanol acetate (108-65-6)

Acute oral toxicity: LD50 rat (male)

8,500 mg/kg

## AZ nLOF 2035 PHOTORESIST (US)



Substance key: 000000065924 REVISION DATE: 10/20/2008

Version Print Date: 10/20/2008

1-Methoxy-2-propanol acetate (108-65-6)

Acute oral toxicity: LD50 rat (female) 10.000 mg/kg

1-Methoxy-2-propanol acetate (108-65-6)

Acute inhalation toxicity LC50 rat

> 4350 ppm

1-Methoxy-2-propanol acetate (108-65-6)

Acute dermal toxicity: LD50 rabbit

> 5,000 mg/kg

# **Section 12 - Ecological information**

**Biodegradability:** No information.

**Fish toxicity:** Based on data from components, this material is classified as:,

Not Harmful (LC50 > 100 mg/L).

**Toxicity of aquatic** Based on data from components, this material is classified as:,

invertebrates: Not Harmful (EC50 greater than 100 mg/L).

**Algae toxicity:** No data available.

1-Methoxy-2-propanol acetate (108-65-6)

**Fish toxicity:** (Fathead minnow)

161 mg/l

1-Methoxy-2-propanol acetate (108-65-6)

Toxicity of aquatic (Daphnia magna)

invertebrates: 400 mg/l

## Section 13 - Disposal considerations

**Product:** Consult local, state, and federal regulations.

For disposal, this material is a flammable hazardous waste

under RCRA.

RCRA hazardous waste: RCRA number: D001

## **Section 14 - Transport information**

Land transport

#### **AZ nLOF 2035 PHOTORESIST** (US)



Substance key: 000000065924

**REVISION DATE: 10/20/2008** Version Print Date: 10/20/2008

DOT:

Not restricted

Sea transport

IMDG:

UN-No: 1993

Proper technical name: FLAMMABLE LIQUID, N.O.S. (2-Methoxy-1-methylethyl

acetate)

Class: 3 Ш Packaging group:

Marine pollutant:

EmS: F-E, S-E

MFAG:

Labels: 3

Air transport

ICAO/IATA-DGR:

UN/ID No.: UN 1993

Proper technical name: FLAMMABLE LIQUID, N.O.S. (2-Methoxy-1-methylethyl

acetate)

Class: 3 Ш Packaging group: Labels: 3

Section 15 - Regulatory information

**TSCA Status:** One or more components of this product are not listed on the

TSCA Inventory. The components, however, are covered by Low Volume Exemptions (LVEs). These LVE-based products may only be used in conventional photolithographic processes consistent with their design. For any applications outside of

this intended purpose, contact the vendor first.

Reactive hazard: no **SARA** (section 311/312):

> Pressure hazard: no Fire hazard: yes Immediate/acute: yes Delayed/chronic: no

**SARA 313 information:** This product is not subject to SARA Title III Section 313

reporting requirements under 40 CFR 372.

Volatile organic Content VOC (g/l): 784 g/l

Method: calculated compounds:

#### AZ nLOF 2035 PHOTORESIST



Substance key: 000000065924

**REVISION DATE: 10/20/2008** Print Date: 10/20/2008 Version

(US)

#### Section 16 - Other information

#### Label information

#### **CAUTION!**

COMBUSTIBLE LIQUID AND VAPOR HARMFUL IF SWALLOWED, INHALED OR ABSORBED THROUGH SKIN Contains material that, based on animal data, can cause skin, eye, and respiratory irritation. Prolonged or repeated overexposure may cause gastric, liver, kidney, and central nervous system effects.

Keep away from heat and flame. Avoid breathing vapor. Avoid contact with skin, eyes, and clothing. Use only with adequate ventilation, and proper protective eyewear, gloves, and clothing. Wash thoroughly after handling. Keep container closed.

In case of contact, flush eyes with plenty of water for 15 minutes. Get medical attention immediately. Flush affected skin areas with water, and wash with mild soap and water. Remove contaminated clothing. If INHALED, remove individual to fresh air. If breathing is difficult, give oxygen. If ingested, give water or milk to dilute stomach contents. Never give anything by mouth to an unconscious person. Get medical attention immediately for ingestion or breathing problems or if skin contact is

In case of fire, use water, alcohol resistant foam, dry chemical, or CO2.

If spilled, wear protective clothing, remove ignition sources, prevent sparks, and ventilate area. Absorb with inert material, collect, and place in a chemical waste container.

Keep sealed in original container. Product must be kept refrigerated until use. Temperature range for refrigeration is 30 to 55 F (- 1 to 13 C). Allow product to reach ambient temperature prior to use. Empty container may contain harmful residue.

The solvent in this product is not photochemically reactive per Rule 102 of the California South Coast Air Quality Management District.

This information is supplied under the OSHA Hazard Communication Standard, 29 CFR 1910.1200, and is offered in good faith based on data available to us that we believe to be true and accurate. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable to the material. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate for that use. No warranty, express or implied, is made regarding the accuracy of this data, the hazards connected with the use of the material, or the results to be obtained from the use thereof. We assume no responsibility for damage or injury from the use of the product described herein. Data provided here are typical and not intended for use as product specifications. (R) and TM indicate trademarks of AZ Electronic Materials USA Corp., its business partners and suppliers.