



Substance key: BBG703W  
Version 1

REVISION DATE: 06/07/2005  
PRINT DATE 11/30/2005

### Section 01 - Product Information

|   |   |
|---|---|
| <b>Identification of the company:</b>           | AZ Electronic Materials USA Corp.<br>70 Meister Avenue<br>Somerville, NJ 08876<br>Telephone No.: 800-515-4164 |
| <b>Information on the substance/preparation</b> | Product Safety: 908-429-3562  |
| <b>Emergency Tel. number:</b>                   | 800-424-9300 CHEMTREC   |

**Trade name:** AZ KWIK STRIP REMOVER 340-0020  
**Material No.:** 18451123170

### Section 02 - Composition information

**Hazardous ingredients:**

| Chemical Name                       | CAS-no. (Trade secret no.) | Concentration [%] |
|-------------------------------------|----------------------------|-------------------|
| Dipropylene glycol monomethyl ether | 34590-94-8                 | 59,00 - 0,00      |
| Tetrahydrothiophene-1,1-dioxide     | 126-33-0                   | 34,00             |
| Polyglycol ether                    | 67829000004-5718P          | 2,00 - 0,00       |

### Section 03 - Hazardous identification

**Emergency overview:** May produce systemic or organ effects with repeated or excessive exposure., Clear, yellow liquid., Solvent odor., Irritating on contact or inhalation., Water soluble.

**Expected route of entry**

**Skin contact:** Contact with liquid and mist.

**Ingestion:** no

**Inhalation:** Inhalation of mist.

**Skin absorption:** yes

**Health effects of exposure:**

**Component information:**



Substance key: BBG703W  
Version 1

REVISION DATE: 06/07/2005  
PRINT DATE 11/30/2005

**Dipropylene glycol monomethyl ether (34590-94-8)**

Dipropylene glycol monomethyl ether is a slight eye irritant. Overexposure of animals to DPGME produces minor liver and kidney effects. In vitro mutagenicity tests have been negative.

**Tetrahydrothiophene-1,1-dioxide (126-33-0)**

Tetrahydrothiophene-1,1-dioxide is a moderate skin and eye irritant. Prolonged or excessive contact may result in severe skin irritation and nervous system effects. Inhalation of excessive mists (aerosols) containing sulfolane may lead to tremors and convulsions. Shows neurotoxicity in animals at high exposures; aggressive behavior, brain, and visual effects are also manifested.

**Polyglycol ether (24938-91-8)**

Polyglycol ether may cause skin, eye, and respiratory irritation.

**Known effects on other illnesses:** Preexisting skin, eye, and respiratory conditions may be aggravated.

**Listed carcinogen:** IARC: NO NTP: NO OSHA: NO

**HMIS:**

Health: 2 Flammability: 1 Reactivity: 0 Personal protection: X

**NFPA:**

Health: 2 Flammability: 1 Reactivity: 0 Special notice: NONE

**Section 04 - First aid measures**

**After inhalation:** Remove victim to fresh air.  
Consult physician if irritation occurs.

**After contact with skin:** Consult physician if exposure is extensive or if irritation occurs.  
Immediately remove contaminated clothing and wash affected area thoroughly with soap and water.

**After contact with eyes:** Flush thoroughly with water for 15 minutes. Get immediate medical help.

**After ingestion:** If person is conscious, give water or milk to dilute stomach contents.  
Never give anything by mouth to an unconscious person.  
Consult physician.

**Advice to doctor / Treatment:** Administer oxygen if there is difficulty in breathing.



Substance key: BBG703W  
Version 1

REVISION DATE: 06/07/2005  
PRINT DATE 11/30/2005

### Section 05 - Fire fighting measures

|   |  |
|---|--|
| <b>Flash point:</b>                           | 236 °F<br>Method: closed cup   |
| <b>Hazardous decomposition products:</b>      | Thermal decomposition may generate carbon dioxide, carbon monoxide, and oxides of sulfur.                        |
| <b>Suitable extinguishing media:</b>          | Carbon dioxide, water, alcohol resistant foam, dry chemical.   |
| <b>Special fire fighting procedure:</b>       | Use self-contained breathing apparatus and full protective clothing. Use water spray to cool drums in fire area. |
| <b>Specific hazards during fire fighting:</b> | Thermal decomposition may generate carbon dioxide, carbon monoxide, and oxides of sulfur.                        |
| <b>Unusual fire and explosion hazards:</b>    | Solvent vapors., Emits toxic fumes under fire conditions.  |

### Section 06 - Accidental release measures

|  |   |
|--|---|
| <b>Steps to be taken in case of spill or leak:</b> | Wearing appropriate personal protective equipment, contain spill, ventilate area of spill or leak, remove all sparking devices or ignition sources, collect onto inert absorbent, and place in a suitable container. Rinse residual with water. |
|--|---|

### Section 07 - Handling and Storage

#### Advice on safe handling:

Avoid breathing vapors and contact with skin, eyes, and clothing.  
Use only with adequate ventilation and proper protective eyewear, gloves, and clothing.  
Wash thoroughly after handling.  
Keep container closed.

#### Further information for storage conditions:

Store at appropriate temperature. See label for details.  
Store in original container.  
Transport and store under dry conditions tightly closed.

### Section 08 - Exposure Control / personal protection

**Respiratory protection:** When heating this material, use engineering controls to provide



Substance key: BBG703W  
Version 1

REVISION DATE: 06/07/2005  
PRINT DATE 11/30/2005

adequate exhaust ventilation or a NIOSH approved respirator.  
Where mist is present, provide local ventilation or a respirator certified for mist by NIOSH.

- Eye protection:** Safety eyewear to protect against splashes.
- Skin and body protection:** Clothing suitable to prevent skin contact.
- Advice on system design:** Use local exhaust ventilation.

### Section 09 - Physical and chemical properties

- Form:** Liquid
- Color:** Clear, yellow
- Odor:** Solvent odor.
- Water solubility:** soluble
- Density:** 1,06 g/cm<sup>3</sup>
- Starts to boil:** 180 °C
- Evaporation number:** Reference substance: n-butyl acetate  
<
- Vapor pressure:** 4 Torr
- Relative vapor density:** > 1
- Loss on drying:** 100 %

### Section 10 - Stability and reactivity

- Hazardous reactions:** Stable.
- Hazardous polymerization:** Will not occur.
- Conditions to avoid:** Avoid contact with oxidizing agents.

### Section 11 - Toxicological information

- Dipropylene glycol monomethyl ether (34590-94-8)**  
**Acute oral toxicity:** LD50 rat  
5.400 mg/kg



Substance key: BBG703W  
Version 1

REVISION DATE: 06/07/2005  
PRINT DATE 11/30/2005

**Tetrahydrothiophene-1,1-dioxide (126-33-0)**

**Acute oral toxicity:** LD50 rat  
1.540 mg/kg

**Tetrahydrothiophene-1,1-dioxide (126-33-0)**

**Acute inhalation toxicity** LC50 rat  
Exposure time: 4 h

**Dipropylene glycol monomethyl ether (34590-94-8)**

**Acute dermal toxicity:** LD50 rabbit

**Tetrahydrothiophene-1,1-dioxide (126-33-0)**

**Acute dermal toxicity:** LD50 rabbit  
4.009 mg/kg

### Section 12 - Ecological information

**Additional ecological information:**

Do not allow to enter soil, waterways or waste water

**Dipropylene glycol monomethyl ether (34590-94-8)**

**Toxicity to fish:** (carp)

### Section 13 - Disposal considerations

**Product:** Consult local, state, and federal regulations.

### Section 14 - Transport information

### Section 15 - Regulatory information

**TSCA Status:** All components of this product are listed on the TSCA Inventory.

**SARA (section 311/312):** Reactive hazard: no  
Pressure hazard: no  
Fire hazard: no  
Immediate/acute: yes  
Delayed/chronic: yes

**SARA 313 information:** This product is not subject to SARA Title III Section 313 reporting requirements under 40 CFR 372.



Substance key: BBG703W  
Version 1

REVISION DATE: 06/07/2005  
PRINT DATE 11/30/2005

**Volatile organic compounds:**      Content VOC (g/l): 625 g/l  
Method: calculated

## Section 16 - Other information

### US State regulatory information

Under the notification requirements of the state of California, this product may be found to contain one or more of the listed chemicals covered by Proposition 65. These are not intentionally included, but can be naturally occurring contaminants and/or raw materials used to produce the product. While we do not analyze expressly for Proposition 65 substances, the possibility of their presence in trace quantities exists. In order to comply with the California law we are therefore providing the following statement: Warning: This product contains chemicals known to the state of California to cause cancer and/or birth defects or other reproductive harm., Ethylene oxide, 1,4-Dioxane

### Label information

**CAUTION!**

Harmful if inhaled, swallowed, or on contact. Contains material that can cause skin, eye, and respiratory irritation; prolonged or repeated overexposure may cause liver, kidney, and central nervous system effects. Based on animal tests, exposure to aerosols of this material may cause aggressive behavior, blood and liver changes, convulsions, and lung effects.

Keep away from heat and flame. Avoid breathing vapor. Avoid contact with skin, eyes, and clothing. Use only with adequate ventilation, and proper protective eyewear, gloves, and clothing. Wash thoroughly after handling. Keep container closed.

In case of contact, flush eyes with plenty of water for 15 minutes. Get medical attention immediately. Flush affected skin areas with water, and wash with mild soap and water. Remove contaminated clothing. If INHALED, remove individual to fresh air. If breathing is difficult, give oxygen. If ingested, give water or milk to dilute stomach contents. Never give anything by mouth to an unconscious person. Get medical attention immediately for ingestion or breathing problems or if skin contact is extensive.

In case of fire, use water, alcohol resistant foam, dry chemical, or CO2.

If spilled, wear protective clothing, remove ignition sources, prevent sparks, and ventilate area. Absorb with inert material, collect, and place in a chemical waste container.

Keep sealed in original container. Protect from heat and light. Store in a cool, dry place. Empty container may contain harmful residue.

The solvent in this product is not photochemically reactive per Rule 102 of the California South Coast Air Quality Management District.



Substance key: BBG703W  
Version 1

REVISION DATE: 06/07/2005  
PRINT DATE 11/30/2005

---

This information is supplied under the OSHA Hazard Communication Standard, 29 CFR 1910.1200, and is offered in good faith based on data available to us that we believe to be true and accurate. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable to the material. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate for that use. No warranty, express or implied, is made regarding the accuracy of this data, the hazards connected with the use of the material, or the results to be obtained from the use thereof. We assume no responsibility for damage or injury from the use of the product described herein. Data provided here are typical and not intended for use as product specifications. (R) and TM indicate trademarks of AZ Electronic Materials USA Corp., its business partners and suppliers.

---