

## SAFETY DATA SHEET

Creation Date 25-Jul-2014

Revision Date 23-May-2017

Revision Number 3

### 1. Identification

**Product Name** 70% Denatured Ethanol, Molecular Biology Grade

**Cat No. :** BP8203-1GAL

**Synonyms** No information available

**Recommended Use** Laboratory chemicals.

**Uses advised against** Not for food, drug, pesticide or biocidal product use

#### Details of the supplier of the safety data sheet

##### **Company**

Fisher Scientific  
One Reagent Lane  
Fair Lawn, NJ 07410  
Tel: (201) 796-7100

##### **Emergency Telephone Number**

Chemtrec US: (800) 424-9300  
Chemtrec EU: 001 (202) 483-7616

### 2. Hazard(s) identification

#### **Classification**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids	Category 2
Acute oral toxicity	Category 4
Acute Inhalation Toxicity - Vapors	Category 4
Serious Eye Damage/Eye Irritation	Category 2
Specific target organ toxicity (single exposure)	Category 1
Target Organs - Respiratory system, Central nervous system (CNS), Optic nerve.	
Specific target organ toxicity - (repeated exposure)	Category 2
Target Organs - Kidney, Liver, Blood.	

#### **Label Elements**

##### **Signal Word**

Danger

##### **Hazard Statements**

Highly flammable liquid and vapor  
Harmful if swallowed  
Causes serious eye irritation  
Harmful if inhaled  
Causes damage to organs  
May cause damage to organs through prolonged or repeated exposure



### Precautionary Statements

#### Prevention

Use personal protective equipment as required  
 Wash face, hands and any exposed skin thoroughly after handling  
 Do not eat, drink or smoke when using this product  
 Use only outdoors or in a well-ventilated area  
 Wear eye/face protection  
 Do not breathe dust/fume/gas/mist/vapors/spray  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use explosion-proof electrical/ventilating/lighting/equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Keep cool

#### Response

IF exposed: Call a POISON CENTER or doctor/physician

#### Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 Call a POISON CENTER or doctor/physician if you feel unwell

#### Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

#### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention

#### Ingestion

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell  
 Rinse mouth

#### Fire

In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

#### Storage

Store in a well-ventilated place. Keep container tightly closed

#### Disposal

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

#### Other hazards

Poison, may be fatal or cause blindness if swallowed. Vapor harmful. Cannot be made non-poisonous.  
 WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

### 3. Composition / information on ingredients

Component	CAS-No	Weight %
Ethyl alcohol	64-17-5	70
Water	7732-18-5	20
Methyl alcohol	67-56-1	5
Isopropyl alcohol	67-63-0	5

### 4. First-aid measures

<b>General Advice</b>	Get medical attention immediately if symptoms occur. Show this safety data sheet to the doctor in attendance. If symptoms persist, call a physician.
<b>Eye Contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Obtain medical attention. Keep eye wide open while rinsing.
<b>Skin Contact</b>	Wash off immediately with plenty of water for at least 15 minutes. Get medical attention immediately if symptoms occur.
<b>Inhalation</b>	Move to fresh air in case of accidental inhalation of vapors. If breathing is difficult, give oxygen. If symptoms persist, call a physician.
<b>Ingestion</b>	Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Do not induce vomiting without medical advice. Obtain medical attention.
<b>Most important symptoms/effects</b>	Breathing difficulties. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting
<b>Notes to Physician</b>	Treat symptomatically

## 5. Fire-fighting measures

<b>Suitable Extinguishing Media</b>	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Cool closed containers exposed to fire with water spray.
<b>Unsuitable Extinguishing Media</b>	Water may be ineffective
<b>Flash Point</b>	15 - 27 °C / 59 - 80.6 °F
<b>Method -</b>	Tag Closed Cup (ASTM D56)
<b>Autoignition Temperature</b>	363 °C / 685.4 °F
<b>Explosion Limits</b>	
<b>Upper</b>	19 vol %
<b>Lower</b>	3.3 vol %
<b>Sensitivity to Mechanical Impact</b>	No information available
<b>Sensitivity to Static Discharge</b>	No information available

### Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated.

### Hazardous Combustion Products

Carbon monoxide (CO) Carbon dioxide (CO<sub>2</sub>)

### Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

### NFPA

**Health**  
3

**Flammability**  
3

**Instability**  
0

**Physical hazards**  
N/A

## 6. Accidental release measures

<b>Personal Precautions</b>	Take precautionary measures against static discharges. Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate ventilation. Use personal protective equipment. Keep people away from and upwind of spill/leak.
<b>Environmental Precautions</b>	Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system. See Section 12 for additional ecological information.
<b>Methods for Containment and Clean</b>	Take precautionary measures against static discharges. Remove all sources of ignition.

**Up** Use spark-proof tools and explosion-proof equipment. Soak up with inert absorbent material. Keep in suitable, closed containers for disposal.

## 7. Handling and storage

**Handling** Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Ensure adequate ventilation. Do not breathe vapors or spray mist. Keep container tightly closed.

**Storage** Keep in properly labeled containers. Keep away from heat and sources of ignition. Keep container tightly closed in a dry and well-ventilated place. Flammables area.

## 8. Exposure controls / personal protection

### Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Ethyl alcohol	STEL: 1000 ppm	(Vacated) TWA: 1000 ppm (Vacated) TWA: 1900 mg/m <sup>3</sup> TWA: 1000 ppm TWA: 1900 mg/m <sup>3</sup>	IDLH: 3300 ppm TWA: 1000 ppm TWA: 1900 mg/m <sup>3</sup>	TWA: 1000 ppm TWA: 1900 mg/m <sup>3</sup>
Methyl alcohol	TWA: 200 ppm STEL: 250 ppm Skin	(Vacated) TWA: 200 ppm (Vacated) TWA: 260 mg/m <sup>3</sup> (Vacated) STEL: 250 ppm (Vacated) STEL: 325 mg/m <sup>3</sup> Skin TWA: 200 ppm TWA: 260 mg/m <sup>3</sup>	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m <sup>3</sup> STEL: 250 ppm STEL: 325 mg/m <sup>3</sup>	TWA: 200 ppm TWA: 260 mg/m <sup>3</sup> STEL: 250 ppm STEL: 310 mg/m <sup>3</sup>
Isopropyl alcohol	TWA: 200 ppm STEL: 400 ppm	(Vacated) TWA: 400 ppm (Vacated) TWA: 980 mg/m <sup>3</sup> (Vacated) STEL: 500 ppm (Vacated) STEL: 1225 mg/m <sup>3</sup> TWA: 400 ppm TWA: 980 mg/m <sup>3</sup>	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m <sup>3</sup> STEL: 500 ppm STEL: 1225 mg/m <sup>3</sup>	TWA: 400 ppm TWA: 980 mg/m <sup>3</sup> STEL: 500 ppm STEL: 1225 mg/m <sup>3</sup>

### Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

**Engineering Measures** Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers are close to the workstation location.

### Personal Protective Equipment

**Eye/face Protection** Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166. Tightly fitting safety goggles. Face-shield.

**Skin and body protection** Wear appropriate protective gloves and clothing to prevent skin exposure. Long sleeved clothing. Apron. Impervious gloves.

**Respiratory Protection** Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

**Hygiene Measures** When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing.

## 9. Physical and chemical properties

<b>Physical State</b>	Liquid
<b>Appearance</b>	Clear Colorless
<b>Odor</b>	sweet Alcohol-like
<b>Odor Threshold</b>	No information available
<b>pH</b>	Not applicable
<b>Melting Point/Range</b>	-144 °C / -227.2 °F
<b>Boiling Point/Range</b>	78.4 °C / 173.1 °F
<b>Flash Point</b>	15 - 27 °C / 59 - 80.6 °F
<b>Method -</b>	Tag Closed Cup (ASTM D56)
<b>Evaporation Rate</b>	No information available
<b>Flammability (solid,gas)</b>	Not applicable
<b>Flammability or explosive limits</b>	
<b>Upper</b>	19 vol %
<b>Lower</b>	3.3 vol %
<b>Vapor Pressure</b>	44.6 mm Hg @ 20 °C (68 °F)
<b>Vapor Density</b>	1.59
<b>Specific Gravity</b>	0.83 – 0.84 @ 20 °C (68 °F)
<b>Solubility</b>	miscible
<b>Partition coefficient; n-octanol/water</b>	No data available
<b>Autoignition Temperature</b>	363 °C / 685.4 °F
<b>Decomposition Temperature</b>	No information available
<b>Viscosity</b>	No information available

## 10. Stability and reactivity

<b>Reactive Hazard</b>	None known, based on information available
<b>Stability</b>	Stable under normal conditions.
<b>Conditions to Avoid</b>	Keep away from open flames, hot surfaces and sources of ignition. Incompatible products. Heat, flames and sparks.
<b>Incompatible Materials</b>	Strong oxidizing agents, Strong acids, Acid anhydrides, Acid chlorides
<b>Hazardous Decomposition Products</b>	Carbon monoxide (CO), Carbon dioxide (CO <sub>2</sub> )
<b>Hazardous Polymerization</b>	Hazardous polymerization does not occur.
<b>Hazardous Reactions</b>	None under normal processing.

## 11. Toxicological information

### Acute Toxicity

#### Product Information

##### Oral LD50

Category 4. ATE = 300 - 2000 mg/kg.

##### Dermal LD50

Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.

##### Vapor LC50

Category 4. ATE = 10 - 20 mg/l.

#### Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethyl alcohol	3450 mg/kg ( Mouse )	Not listed	20000 ppm/10H ( Rat )
Water	LD50 > 90 mL/kg ( Rat )	Not listed	Not listed
Methyl alcohol	<b>Calc. ATE 60 mg/kg</b> LD50 > 1187 – 2769 mg/kg ( Rat )	<b>Calc. ATE 60 mg/kg</b> LD50 = 17100 mg/kg ( Rabbit )	<b>Calc. ATE 0.6 mg/L (vapours) or 0.5 mg/L (mists)</b> LC50 = 128.2 mg/L ( Rat ) 4 h
Isopropyl alcohol	5840 mg/kg ( Rat )	13900 mg/kg ( Rat ) 12870 mg/kg ( Rabbit )	72.6 mg/L ( Rat ) 4 h

**Toxicologically Synergistic Products** No information available

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Irritation** Irritating to eyes

**Sensitization** No information available

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Ethyl alcohol	64-17-5	Group 1	Known	A3	X	Not listed
Water	7732-18-5	Not listed	Not listed	Not listed	Not listed	Not listed
Methyl alcohol	67-56-1	Not listed	Not listed	Not listed	Not listed	Not listed
Isopropyl alcohol	67-63-0	Not listed	Not listed	Not listed	Not listed	Not listed

*IARC: (International Agency for Research on Cancer)*

*IARC: (International Agency for Research on Cancer)*

*Group 1 - Carcinogenic to Humans*

*Group 2A - Probably Carcinogenic to Humans*

*Group 2B - Possibly Carcinogenic to Humans*

*A1 - Known Human Carcinogen*

*A2 - Suspected Human Carcinogen*

*A3 - Animal Carcinogen*

*ACGIH: (American Conference of Governmental Industrial Hygienists)*

*ACGIH: (American Conference of Governmental Industrial Hygienists)*

*OSHA: (Occupational Safety & Health Administration)*

*OSHA: (Occupational Safety & Health Administration)*

*X - Present*

*Mexico - Occupational Exposure Limits - Carcinogens*

*Mexico - Occupational Exposure Limits - Carcinogens*

*A1 - Confirmed Human Carcinogen*

*A2 - Suspected Human Carcinogen*

*A3 - Confirmed Animal Carcinogen*

*A4 - Not Classifiable as a Human Carcinogen*

*A5 - Not Suspected as a Human Carcinogen*

**Mutagenic Effects** Mutagenic effects have occurred in humans.

**Reproductive Effects** Adverse reproductive effects have occurred in humans.

**Developmental Effects** Substances known to cause developmental toxicity in humans.

**Teratogenicity** Teratogenic effects have occurred in humans.

**STOT - single exposure** Respiratory system Central nervous system (CNS) Optic nerve  
**STOT - repeated exposure** Kidney Liver Blood

**Aspiration hazard** No information available

**Symptoms / effects, both acute and delayed** Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

**Endocrine Disruptor Information** No information available

**Other Adverse Effects** Tumorigenic effects have been reported in experimental animals.

## 12. Ecological information

### Ecotoxicity

Do not empty into drains.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Ethyl alcohol	EC50 (72h) = 275 mg/l (Chlorella vulgaris)	Fathead minnow (Pimephales promelas) LC50 = 14200 mg/l/96h	Photobacterium phosphoreum: EC50 = 34634 mg/L/30 min Photobacterium phosphoreum: EC50 = 35470 mg/L/5 min	EC50 = 9268 mg/L/48h EC50 = 10800 mg/L/24h
Methyl alcohol	Not listed	Pimephales promelas: LC50	EC50 = 39000 mg/L 25 min	EC50 > 10000 mg/L 24h

		> 10000 mg/L 96h	EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min	
Isopropyl alcohol	EC50: > 1000 mg/L, 72h (Desmodesmus subspicatus) EC50: > 1000 mg/L, 96h (Desmodesmus subspicatus)	LC50: > 1400000 µg/L, 96h (Lepomis macrochirus) LC50: = 11130 mg/L, 96h static (Pimephales promelas) LC50: = 9640 mg/L, 96h flow-through (Pimephales promelas)	= 35390 mg/L EC50 Photobacterium phosphoreum 5 min	13299 mg/L EC50 = 48 h 9714 mg/L EC50 = 24 h

**Persistence and Degradability** Persistence is unlikely based on information available.

**Bioaccumulation/ Accumulation** No information available.

**Mobility** Will likely be mobile in the environment due to its volatility.

Component	log Pow
Ethyl alcohol	-0.32
Methyl alcohol	-0.74
Isopropyl alcohol	0.05

### 13. Disposal considerations

**Waste Disposal Methods** Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Methyl alcohol - 67-56-1	U154	-

### 14. Transport information

#### DOT

UN-No UN1170  
 Proper Shipping Name ETHANOL SOLUTION  
 Hazard Class 3  
 Packing Group II

#### TDG

UN-No UN1170  
 Proper Shipping Name ETHANOL SOLUTION  
 Hazard Class 3  
 Packing Group II

#### IATA

UN-No UN1170  
 Proper Shipping Name ETHANOL SOLUTION  
 Hazard Class 3  
 Packing Group II

#### IMDG/IMO

UN-No UN1170  
 Proper Shipping Name ETHANOL SOLUTION  
 Hazard Class 3  
 Packing Group II

### 15. Regulatory information

All of the components in the product are on the following Inventory lists: X = listed

#### International Inventories

Component	TSCA	DSL	NDSL	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
Ethyl alcohol	X	X	-	200-578-6	-		X	X	X	X	X

Water	X	X	-	231-791-2	-		X	-	X	X	X
Methyl alcohol	X	X	-	200-659-6	-		X	X	X	X	X
Isopropyl alcohol	X	X	-	200-661-7	-		X	X	X	X	X

**Legend:**

X - Listed

E - Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.

F - Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.

N - Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.

P - Indicates a commenced PMN substance

R - Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.

S - Indicates a substance that is identified in a proposed or final Significant New Use Rule

T - Indicates a substance that is the subject of a Section 4 test rule under TSCA.

XU - Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B)).

Y1 - Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.

Y2 - Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

**U.S. Federal Regulations**

TSCA 12(b) Not applicable

**SARA 313**

Component	CAS-No	Weight %	SARA 313 - Threshold Values %
Methyl alcohol	67-56-1	5	1.0
Isopropyl alcohol	67-63-0	5	1.0

**SARA 311/312 Hazard Categories**

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

CWA (Clean Water Act) Not applicable

**Clean Air Act**

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Methyl alcohol	X		-

OSHA Occupational Safety and Health Administration  
Not applicable**CERCLA**

Component	Hazardous Substances RQs	CERCLA EHS RQs
Methyl alcohol	5000 lb	-

**California Proposition 65** This product contains the following proposition 65 chemicals Ethyl alcohol is only a considered a Proposition 65 developmental hazard when it is ingested as an alcoholic beverage

Component	CAS-No	California Prop. 65	Prop 65 NSRL	Category
Ethyl alcohol	64-17-5	Development (alcoholic beverages only)	-	Developmental Carcinogen
Methyl alcohol	67-56-1	Developmental	-	Developmental

**U.S. State Right-to-Know Regulations**

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island



Ethyl alcohol	X	X	X	X	X
Water	-	-	X	-	-
Methyl alcohol	X	X	X	X	X
Isopropyl alcohol	X	X	X	-	X

**U.S. Department of Transportation**

Reportable Quantity (RQ): N  
 DOT Marine Pollutant N  
 DOT Severe Marine Pollutant N

**U.S. Department of Homeland Security**

This product does not contain any DHS chemicals.

**Other International Regulations**

**Mexico - Grade** Serious risk, Grade 3

## 16. Other information

**Prepared By** Regulatory Affairs  
 Thermo Fisher Scientific  
 Email: EMSDS.RA@thermofisher.com

**Creation Date** 25-Jul-2014  
**Revision Date** 23-May-2017  
**Print Date** 23-May-2017  
**Revision Summary** This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of SDS**