## **BREWER SCIENCE INC.** SAFETY DATA SHEET

This Safety Data Sheet has been prepared to comply with the EC Directive, Canadian WHMIS and the OSHA Hazard Communication Standard

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

Product Name: ProTEK®B3 Primer

Manufacturer: Brewer Science, Inc. 2401 Brewer Drive Rolla, MO 65401

Information Phone Number: (573) 364-0300 Fax: (573) 368-3318 Email: msds@brewerscience.com **Emergency Phone Number:** Chemtrec Domestic North America: 800-424-9300 Chemtrec International: 703-527-3887 **SDS Date of Preparation**: 8/28/07 Product Use: Primer

# **SECTION 2: HAZARDS IDENTIFICATION**

Liquid with a solvent odor.

EMERGENCY OVERVIEW: Flammable liquid and vapor. May cause eye, skin, and respiratory irritation. May cause headache, dizziness, nausea and other symptoms of central nervous system depression.

EU Preparation Classification (1999/45/EC): Flammable R10

#### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS# / EINECS#	%	EU Classification (67/548/EEC)
1-Methoxy-2-propanol	107-98-2 / 203-539-1	95-100	R10
(Propylene glycol monomethyl ether, PGME)			
Deionized Water	7732-18-5 / 231-791-2	<1-5	No EU Classification or R phrase
Additive	Proprietary	<1	C R22, R34

See Section 16 for further information on EU Classification.

#### **SECTION 4: FIRST AID MEASURES**

Eye: Rinse thoroughly with water for at least 15 minutes, holding the eye lids open to be sure the material is washed out. Get immediate medical attention.

Skin: Remove contaminated clothing. Wash contact area thoroughly with soap and water. Get medical attention if irritation or symptoms of exposure develop. Launder clothing before re-use.

Inhalation: Remove victim to fresh air. Give artificial respiration if needed. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.

Ingestion: Do not induce vomiting unless directed to do so by medical personnel. Keep the victim calm and warm. Get immediate medical attention.

# **SECTION 5: FIRE FIGHTING MEASURES**

Extinguishing Media: Use water fog or spray, alcohol foam, carbon dioxide or dry chemical.

Prepared By:	Safety & Environmental Units
Approved By:	Safety & Environmental Units
Issue/Revision Date	F.7.6.3183.D/ 12/14/09

**Special Fire Fighting Procedures:** Wear an approved, positive pressure, self-contained breathing apparatus and full protective clothing. Cool fire exposed containers with water.

Unusual Fire Hazards: Vapors are heavier than air and may travel along surfaces to remote ignition sources and flash back. Vapors may form explosive mixtures with air in confined areas.

Hazardous Decomposition Products: Oxides of carbon, silicon and nitrogen and unknown materials.

# SECTION 6: ACCIDENTAL RELEASE MEASURES

**Spill:** Remove all ignition sources such as open flames, spark producing equipment, pilot lights, etc. Wear appropriate protective clothing to prevent eye and skin contact including impervious gloves, safety goggles and respirator if needed. Ventilate area. Cover with an inert absorbent material and collect into an appropriate container for disposal. Report spills and releases as required to appropriate authorities.

# SECTION 7: HANDLING AND STORAGE

**Handling:** Avoid breathing vapors, aerosols and mists. Use with adequate ventilation. Avoid contact with the eyes, skin and clothing. Always wear impervious gloves, chemical safety goggles and protective clothing when handling this material. Wash thoroughly after handling. Do not eat, drink or smoke in the work area. Keep product away from heat, sparks, flames and all other sources of ignition. No smoking in storage or use areas. Keep containers closed when not in use.

Storage: Store in a cool, dry, well-ventilated location away from incompatible materials. Keep containers closed when not in use.

Chemical Name	Exposure Limits
1-Methoxy-2-propanol	100 ppm TLV-TWA, 150 ppm TLV-STEL
	100 ppm DFG MAK
	100 ppm UK-TWA, 150 ppm UK-STEL skin
	100 ppm EU-TWA, 150 ppm EU-STEL skin
Deionized Water	None Established
Additive	None Established

#### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

**Ventilation:** Use with adequate general or local exhaust ventilation to maintain exposure levels below the occupational exposure limits. Use explosion proof electrical equipment and wiring where required.

**Respiratory Protection:** If needed, an approved respirator with organic vapor cartridges may be used. For higher exposures, a supplied air respirator may be required. Respirator selection and use should be based on contaminant type, form and concentration. Follow applicable regulations and good Industrial Hygiene practice.

Skin Protection: Impervious gloves are recommended. Based on available test data, 4H or Silver Shield gloves are suggested.

Eye Protection: Chemical safety goggles recommended.

**Other Protective Equipment:** Impervious clothing is recommended to prevent skin contact and contamination of personal clothing. An eye wash facility and safety shower should be available in the work area.

# SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance and Odor: Liquid with a solvent odor. pH: Not available Boiling Point: 120°C Vapor Pressure: 12.5 mmHg @ 25°C (PGME) Vapor Density: 3.12 (PGME) Flash Point: 32°C (90°F) (PGME)

Specific Gravity: Not available Melting Point: Not Applicable Water Solubility: Partially Soluble Evaporation Rate: Not available Flammable Limits: LEL: 0.8 vol % (Additive) UEL: 13.8 vol % (PGME)

Prepared By:	Safety & Environmental Units
Approved By:	Safety & Environmental Units
Issue/Revision Date	F.7.6.3183.D/ 12/14/09
0	

# SECTION 10: STABILITY AND REACTIVITY

Stability: Stable: X Unstable:

Incompatibility/Conditions to Avoid: Strong oxidizing agents, acids and bases. Keep away from heat, sparks, flames and other sources of ignition.

Hazardous Decomposition Products: Oxides of carbon, silicon and nitrogen and unknown materials.

Hazardous Polymerization: May Occur: Will not occur: X

### SECTION 11: TOXICOLOGICAL INFORMATION

#### **Potential Health Effects:**

Eye: May cause moderate eye irritation. Corneal injury is possible.

Skin: May cause irritation. 1-Methoxy-2-propanol may be absorbed through the skin causing symptoms of headache, dizziness, nausea, and drowsiness.

**Inhalation:** Inhalation of vapors, mists, or aerosols may cause nose and throat irritation with the possibility of central nervous system depression. Symptoms of central nervous system depression include headache, dizziness, drowsiness, nausea and unconsciousness.

**Ingestion:** Swallowing may cause gastrointestinal irritation and central nervous system depression with symptoms similar to those described under inhalation.

Chronic Hazards: Chronic exposure may cause kidney or liver effects based on studies with laboratory animals.

**Carcinogen Status:** None of the components of this product are listed as carcinogens by OSHA, IARC, ACGIH, the EU Dangerous Substances Directive, or NTP.

Medical Conditions Aggravated by Exposure: Pre-existing skin diseases.

## Acute Toxicity Values:

1-Methoxy-2-propanol: Oral rat LD50 - 5660 mg/kg; Inhalation rat LC50 - 10,000 ppm/5 hr; Skin rabbit LD50 - 13 gm/kg Deionized Water: No data available

Additive: Oral Rat LD50: 1780 mg/kg; Skin Rabbit LD50: 4 mL/kg;

# **SECTION 12: ECOLOGICAL INFORMATION**

1-Methoxy-2-propanol: LC50 for fathead minnow is 20800 mg/L and for daphnia magna is 23300 mg/L.

#### **SECTION 13: DISPOSAL INFORMATION**

Dispose in accordance with all local, state and federal regulations.

# SECTION 14: TRANSPORT INFORMATION

ERG #129

DOT Shipping Name: 1-Methoxy-2-propanol Solution DOT Hazard Class: 3, PG III UN Number: UN3092 DOT Labels Required (49CFR172.101): Flammable Liquid Hazardous Substance (49CFR172.101): None Reportable Quantity: N/A

IATA Shipping Name: 1-Methoxy-2-propanol Solution IATA Hazard Class: 3, PG III

Prepared By:	Safety & Environmental Units
Approved By:	Safety & Environmental Units
Issue/Revision Date	F.7.6.3183.D/ 12/14/09

# SECTION 15: REGULATORY INFORMATION

#### **U.S. FEDERAL REGULATIONS:**

**CERCLA 103 Reportable Quantity:** This product is not subject to reporting under CERCLA. Some states have more stringent reporting requirements. Report all spills in accordance with local, state and federal regulations.

#### SARA TITLE III:

Hazard Category for Section 311/312: Acute Health, Fire Hazard

Section 313 Toxic Chemicals: This product contains the following chemicals subject to SARA Title III Section 313 Reporting requirements: None

Section 302 Extremely Hazardous Substances (TPQ): None

EPA Toxic Substances Control Act (TSCA) Status: All of the components of this product are listed on TSCA.

#### STATE REGULATIONS:

California Proposition 65: This product contains the following substances known to the State of California to cause cancer and/or reproductive harm: None known

# **INTERNATIONAL REGULATIONS:**

#### European Community Labeling:

R10 Flammable
S51 Use only in well ventilated areas.

SECTION 16: O	THER INFORMATION
---------------	------------------

HMIS Ratings:	Health - 1	Flammability - 3	Reactivity - 0
NFPA Ratings:	Health - 1	Flammability - 3	Reactivity - 0

## **SDS Revision History:**

8/28/07: New SDS.

2/8/08: Updated format for REACH, updated wording for Carcinogen status, CERCLA, and California Proposition 65 statement, removed references to NIOSH, changed MSDS to SDS.

2/9/09: Added ACGIH to carcinogen status.

12/14/09: Updated EU Classification in Section 3. Updated PGME Exposure limits in Section 8. Updated Physical data in Section 9. Updated Acute toxicity value for Skin rabbit in Section 11. Rearranged order of components.

#### EU Classes and Risk Phrases for Reference (See Sections 2 and 3):

C Corrosive R10 Flammable R22 Harmful if swallowed. R34 Causes burns.

\_\_\_\_\_

This above information is believed to be correct but does not propose to be all inclusive and shall be used only as a guide. Brewer Science, Inc. shall not be held liable for any damage resulting from handling or from contact with the above product.

Prepared By:	Safety & Environmental Units
Approved By:	Safety & Environmental Units
Issue/Revision Date	F.7.6.3183.D/ 12/14/09